1. (Currently Amended) A cleaning sheet having a cleaning surface comprising a

cleaning area for cleaning a piled surface and a low-friction area which adjoins said cleaning

area,

wherein said cleaning area has a first sheet as a scraping part and second sheet as a dust-

holding part, wherein the first and second sheets extend in the same direction;

said first sheet is an air-laid nonwoven fabric comprising at least one

thermoplastic resin selected from the group consisting of a polyolefin, polyamide,

polyester and a fluororesin, and the air-laid surface comprises numerous fibers having a

fineness of 23 to 200 dtex;

said second sheet comprises spun-laced, air-through or spun-bonded nonwoven

fabric;

said scraping part of the first sheet having on the surface thereof numerous fibers

that edges into the pile of a piled surface and scrapes fibrous dust present in said pile, said

fibers mainly comprising fibers constituting the air-laid nonwoven fabric, and

said dust-holding part of the second sheet holds the scraped fibrous dust by having the

fibrous dust physically entangled therewith;

wherein said cleaning area having a coefficient of static friction of 0.1 to 4.0 against wool

press felt (JIS L3201 R33W),

wherein said cleaning area contains the air-laid nonwoven fabric, and

Application No. 09/974,853

Amendment dated September 22, 2005

After Final Office Action of June 22, 2005

said low-friction area comprises a film or a nonwoven fabric, and wherein said low-

Docket No.: 0445-0310P

friction area has a coefficient of static friction of 0.01 to 1.0 against wool press felt (JIS L3201

R33W).

2. (Canceled)

3. (Previously Presented) The cleaning sheet according to claim 1, wherein an area ratio

of said low-friction area to said cleaning surface is 10 to 60%.

4. (Original) The cleaning sheet according to claim 1, wherein said low-friction area is

disposed on one side of said cleaning surface across the cleaning direction of said cleaning

surface.

5. (Original) The cleaning sheet according to claim 4, wherein said low-friction area is

disposed on both sides of said cleaning surface across the cleaning direction of said cleaning

surface.

6-14. (**Canceled**)

15. (Previously presented) The cleaning sheet according to claim 1, wherein said first

sheet is disposed on said second sheet.